

CATEGORY: Dredging

TMT Hydraulic LP Jet Pump

Engineered Tooling Solutions *FAST*



The TMT Hydraulic Low Pressure Jet Pump uses a hydro hydraulically driven centrifugal pump, which is connected to a custom designed nozzle by a flexible two (2) inch hose. This jetting pump is typically fitted to the TMT Tooling Skid (TMT-NSS-200 Typhoon MK2 Fluid Transfer Skid) and forms part of the TMT dredging and jetting suite of subsea tools. It is easily handled by ROV manipulators using the integrated D-handle.

The TMT Hydraulic LP Jet Pump is excellent for cleaning drill cuttings from around sensitive completion areas. TMT can customise this tool to your requirements.

Features:

- Fast and efficient jetting
- Smooth and reliable hydraulic pump
- Corrosion resistant materials
- Easy to install & remove
- Stainless steel filter grill
- Integrated D-handle for ROV control

Specifications:

- | | |
|------------------------|---------------------------------|
| • Dimensions (approx.) | 410L x235W x253Hmm |
| • Max Flow Rate | 214gpm |
| • Max Pressure | 150psi |
| • Ports | 2" NPT inlet
1" NPT outlet |
| • Hydraulic Ports | 1/2" NPT inlet
3/4" NPT tank |
| • Hose | 2" (51mm) |

Specifications subject to change without notice. All rights reserved.